

CAPACITIES

Year	Model	Engine		Engine Oil with	Transmission			Transfer	Drive Axle		Fuel	Cooling
		Displacement	Engine	Filter	(pts.)			Case	Front	Rear	Tank	System
		Liters (cc)	ID/VIN	(qts.)	4-Spd	5-Spd	Auto.	(pts.)	(pts.)	(pts.)	(gal.)	(qts.)
1995 (cont.)	C3500	7.4 (7440)	N	6.0	—	⑩	②	—	—	③	⑥	25.0 ⑪
	K1500	4.3 (4293)	Z	5.0	—	⑩	②	—	—	③	⑥	11.0
	K1500	5.0 (4999)	H	5.0	—	⑩	②	—	—	③	⑥	18.0
	K1500	5.7 (5735)	K	5.0	—	⑩	②	—	—	③	⑥	18.0
	K1500	6.5 (6473)	F	7.0	—	⑩	②	—	—	③	⑥	26.5
	K1500	7.4 (7440)	N	6.0	—	⑩	②	—	—	③	⑥	25.0 ⑪
	K2500	4.3 (4293)	Z	5.0	—	⑩	②	—	—	③	⑥	11.0
	K2500	5.0 (4999)	H	5.0	—	⑩	②	—	—	③	⑥	18.0
	K2500	5.7 (5735)	K	5.0	—	⑩	②	—	—	③	⑥	18.0
	K2500	6.5 (6505)	P	7.0	—	⑩	②	—	—	③	⑥	26.5
	K2500	6.5 (6505)	S	7.0	—	⑩	②	—	—	③	⑥	26.5
	K2500	6.5 (6473)	F	7.0	—	⑩	②	—	—	③	⑥	26.5
	K2500	7.4 (7440)	N	6.0	—	⑩	②	—	—	③	⑥	25.0 ⑪
	K3500	5.0 (4999)	H	5.0	—	⑩	②	—	—	③	⑥	18.0
	K3500	5.7 (5735)	K	5.0	—	⑩	②	—	—	③	⑥	18.0
	K3500	6.5 (6505)	P	7.0	—	⑩	②	—	—	③	⑥	26.5
	K3500	6.5 (6505)	S	7.0	—	⑩	②	—	—	③	⑥	26.5
	K3500	6.5 (6473)	F	7.0	—	⑩	②	—	—	③	⑥	26.5
	K3500	7.4 (7440)	N	6.0	—	⑩	②	—	—	③	⑥	25.0 ⑪
	Suburban	5.7 (5735)	K	5.0	—	—	②	10	4.0	③	25.0 ⑧	18.0
	Suburban	6.5 (6505)	P	7.0	—	⑩	②	—	—	③	⑥	25.0
	Suburban	6.5 (6505)	S	7.0	—	⑩	②	—	—	③	⑥	25.0
	Suburban	7.4 (7440)	N	6.0	—	—	②	10	4.0	③	25.0 ⑧	24.5

① 85mm: 3.5 pts.; 117mm: 8.4 pts.

② 350C trans: 6.3 pts.

THM400 and 4L80 trans: 9.0 pts.

THM700 R4 and 4L60 trans: 10.0 pts.

③ 8.5" ring gear: 4.2 pts.

9.5" ring gear: 6.5 pts.

9.75" ring gear: 6.0 pts.

10.5" ring gear: 6.5 pts.

④ Available with optional 31 gallon tank.

⑤ Available with optional 32 gallon tank.

⑥ Std. available with 25 and 34 gallon tanks.

Chassis cab available with 22, 30 and 34 gallon tanks.

⑦ Short bed: 16 gals.; Long bed: 20 gals.

⑧ Available with 31 and 40 gallon tanks.

⑨ Available with 32 and 41 gallon tanks.

⑩ New Venture gear 4500: 8.0 pts.

New Venture gear 5LM60: 4.4 pts.

⑪ 3500HD: 28.5 qts. capacity